

OTICON | Xceed

OTICON | Opn S

## Velox S™ Product Matrix for Xceed & Opn S™




Call  
Absolute Hearing Solutions  
For Hearing Aid Deals  
614-452-4280  
[www.absolutehearingsolutions.com](http://www.absolutehearingsolutions.com)

**oticon**  
PEOPLE FIRST



# Opn S Models and Styles




	Opn S 1	Opn S 2	Opn S 3
<b>BTE Styles: miniRITE, miniRITE T, miniRITE R, BTE PP</b>	•	•	•
<b>Speech Understanding</b>			
OpenSound Navigator™	Level 1	Level 2	Level 3
Balancing power effect	100%	50%	50%
Max. noise removal	9 dB	5 dB	3 dB
OpenSound Optimizer™	•	•	•
Speech Guard™ LX	Level 1	Level 2	Level 3
Spatial Sound™ LX	4 estimators	2 estimators	2 estimators
Soft Speech Booster LX	•	•	•
<b>Sound Quality</b>			
Speech Rescue™	•	•	•
Clear Dynamics	•	•	-
Spatial Noise Management	•	•	-
Fitting Bandwidth (accessed in software)	10 kHz	8 kHz	8 kHz
Processing Channels	64	48	48
Bass Boost (streaming)	•	•	•
<b>Listening Comfort</b>			
Transient Noise Management	4 configurations	On/Off	On/Off
Feedback shield LX	•	•	•
Wind Noise Management	•	•	•
Binaural Coordination	•	•	•
<b>Personalization &amp; Optimizing Fitting</b>			
YouMatic™ LX	3 configurations	2 configurations	1 configuration
Fitting Bands	16	14	12
Multiple Directionality Options	•	•	•
Adaptation Management	•	•	•
Oticon Firmware Updater	•	•	•
Fitting Formulas	VAC+, NAL-NL1 + 2, DSL v.5.0	VAC+, NAL-NL1 + 2, DSL v.5.0	VAC+, NAL-NL1 + 2, DSL v.5.0
Tinnitus SoundSupport™	•	•	•
CROS/BiCROS support	•	•	-
<b>Connecting to the World</b>			
Stereo streaming (2.4 GHz)	•	•	•
Made for iPhone®	•	•	•
Oticon ON App	•	•	•
ConnectClip	•	•	•
Remote Control 3.0	•	•	•
TV Adapter 3.0	•	•	•
Phone Adapter 2.0	•	•	•

Note: For Opn S hearing devices, the effect and availability of features varies with hearing aid style and prescriptions. For information on compatibility, please visit [Oticon.com/support](https://www.oticon.com/support)



# Xceed Models and Styles



	Xceed 1	Xceed 2	Xceed 3
	BTE Styles: Super Power (SP) 13 battery; Ultra Power (UP) 675 battery		
Speech Understanding	OpenSound Navigator™	Level 1	Level 2
	Balancing power effect	100%	50%
	Max. noise removal	9 dB	5 dB
	OpenSound Optimizer™	•	•
	Noise Reduction LX	-	-
	Multiband Adaptive Directionality LX	-	-
	OpenSound Booster™	•	•
	Speech Guard™ LX	Level 1	Level 3
	Single Compression LX	-	-
	Speech Rescue™ LX	•	•
Sound Quality	Clear Dynamics	•	-
	Spatial Noise Management	•	-
	Processing Channels	48	48
	Bass Boost (streaming)	•	•
Listening Comfort	Transient Noise Management	4 configurations	3 configurations
	Feedback shield LX	•	•
	Wind Noise Management	•	•
Personalization & Optimizing Fitting	YouMatic™ LX, Noise Reduction Levels	3 configurations	2 configurations
	Fitting Bands	14	12
	Multiple Directionality Options	•	•
	Adaptation Management	•	•
	Oticon Firmware Updater	•	•
	VC range and step size	•	•
	Fitting Formulas	DSE, VAC+, NAL-NL1 + 2, DSL v5.0	DSE, VAC+, NAL-NL1 + 2, DSL v5.0
Connecting to the World	Stereo streaming (2.4 GHz)	•	•
	Oticon ON App	•	•
	ConnectClip	•	•
	Remote Control 3.0	•	•
	TV Adapter 3.0	•	•
	Phone Adapter 2.0	•	•
	Amigo FM	•	•
	Tinnitus SoundSupport™	•	•
CROS/ BiCROS support	•	•	
Bimodal fitting panel	•	•	

Note: For Xceed hearing devices, the effect and availability of features varies with hearing aid style and prescriptions. For information on compatibility, please visit [Oticon.com/support](https://www.oticon.com/support)



# Oticon Velox S Style Options

**NEW** More power. More choices. More freedom. Two new power styles to choose from: Xceed BTE Super Power & Xceed BTE Ultra Power

**NEW** Oticon CROS - world's first CROS/BiCROS solution with the open sound experience and TwinLink™ dual streaming.

All miniRITE and BTE styles offer patients a discreet hearing aid with a wealth of new features and functionality, including 2.4 GHz wireless technology and Made for iPhone® functionality.

The rechargeable miniRITE R is powered by state-of-the-art lithium-ion battery technology for a full day's charge, providing ease of use with fast charging times.


## Models




miniRITE miniRITE T miniRITE R BTE PP Xceed UP & SP Oticon CROS

## miniFit receivers and Power Receiver Molds

Select between three receivers with different output performance, with lengths 0-5 for non power speakers and 1-5 for power. The 105 receiver requires a custom Power Receiver Mold.



### Cordea miniFit\*



\*Not for SP/UP models

## Earpieces

miniFit earpieces include standard domes, MicroMold, and LiteTip. Custom earpieces are available in acrylic, soft silicone or VarioTherm® material.



## All style colors

